



## National Center for Forensic Science

Attn: Mary Williams  
PO Box 162367  
Orlando, FL 32816  
Phone: (407) 823-6469  
Fax: (407) 823-3162  
Email: [mary.williams@ucf.edu](mailto:mary.williams@ucf.edu)

Make payment payable to:  
**University of Central Florida**

University of Central Florida FEID:  
59-2924021

## Ignitable Liquids Reference Collection (ILRC)

### Sample Ordering Procedures

Samples of ignitable liquids can be purchased by filling out the Order form. A list of available ignitable liquids can be found in the ILRC database: [www.ncfs.org/databases](http://www.ncfs.org/databases). Completed order forms can be sent to the NCFS via fax, mail, or email.

### Payment Policy

Sample cost is \$5.00/sample plus \$7.50/shipment for shipping and handling to destinations in the continental US. For large orders or those outside the continental US contact NCFS for a quote. Payment terms are net 30 days. Payment must be in the form of check or purchase order payable to: **University of Central Florida**.

### Ignitable Liquid Samples

Sample volumes of 400 $\mu$ l are adsorbed onto activated charcoal contained in 1/2 dram vials.

### Shipping Policy

All orders are shipped via UPS-Ground. Orders will be filled within one week of receipt of purchase order or payment. In transit delivery times for UPS-Ground from Orlando vary from one to seven days. Material Safety Data Sheets (MSDS) are available on the ILRC database.

Contact the NCFS for additional information.

**Disclaimer:** The intent of the ILRC database with its associated liquid repository is to provide a **FREE** searchable resource that allows a laboratory to isolate an ignitable liquid of interest for inclusion into an in-house reference collection.

Commercial products are obtained from manufacturers and distributors then repackaged for distribution using the product name. The database is designed for screening purposes only; it does not replace ASTM requirements for an in-house reference collection.

Classification of the ignitable liquids within the database parallels ASTM E1618-06 and is a consensus from a committee of practicing fire debris analysts.

